

VECTOR[®]

Service, Performance, Reliability™



*The industry's
most trusted supplier
of Specialty Films*

TECHNICAL DATA:

Vector's Metallized Polyester

Chrome Mirror and Gold Mirror - PERMANENT ADHESIVE

A 2.0 mil. metallized polyester with 207-4832 permanent acrylic pressure sensitive adhesive on a 78# liner designed for computerized graphic sign cutting machines.

Applications	These products are recommended for applications requiring a high quality pressure sensitive film. Bright silver and gold polyester can be used for architectural signage, commercial or retail signage and point of purchase graphics.	
Thickness	Film	2.0 mils.
	Adhesive	0.8 to 1.2 mils.
	Liner	4.5 mils.
	(Thickness variance +/- 10%)	
Dimensional Stability	Good.	
Temperature Ranges	Minimum application temperature is +50°F. Service temperature range is -40°F to +250°F.	
Expected Lifetime Exterior	Silver	Up to 2 years under normal conditions.
	Gold	Not recommended for exterior applications.
Adhesion	To stainless steel - 48 oz./in. To painted metal - 48 oz./in. PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.	
Water Resistance	Excellent	
Humidity Resistance	Excellent	
Storage Stability	1-year shelf life when stored at 70°F and 50% relative humidity.	
Product Codes	V1846	Chrome Poly
	V1848	Gold Poly



VECTOR[®]

925 Saw Mill River Rd., Yonkers, NY 10710

T: 914-963-8500 or 800-345-6027 • F: 914-963-9125 or 888-590-9125

www.vectorgraphics.com • sales@vectorgraphics.com