

VECTOR[®]

Service, Performance, Reliability™



*The industry's
most trusted supplier
of Specialty Films*

TECHNICAL DATA:

ProV-5 Series

Intermediate Polished Vinyl

The ProV-5 Series is a 3.0 mil polished polymeric flexible calendered vinyl with 200-4981 permanent acrylic pressure sensitive adhesive laminated to a 78# clay coated liner. Commonly used on computer programmable sign cutting machines

Applications	This product is recommended for outdoor and indoor uses where a high quality marking film-requiring flexibility, durability and resistance to sunlight is required. These films can be used for architectural signage, commercial-retail signage, point-of-purchase graphics and decals.
Thickness	Film 3.0 mils Adhesive 0.8 to 1.2 mil Liner 4.5 mils (Thickness variance +/- 10%)
Dimensional Stability	Good.
Temperature Ranges	Minimum application temperature is +40°F. Service temperature range is -40°F to +200°F.
Expected Lifetime Exterior	Up to 5 years under normal exposure conditions.
Adhesion	To stainless steel - 48 oz./in. PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.
Water Resistance	Limited immersion resistance. Test for specific application.
Humidity Resistance	Good
Storage Stability	1-year shelf life when stored at 70°F and 50% relative humidity.



VECTOR[®]

925 Saw Mill River Rd., Yonkers, NY 10710

T: 914-963-8500 or 800-345-6027 • F: 914-963-9125 or 888-590-9125

www.vectorgraphics.com • sales@vectorgraphics.com