

VECTOR[®]

Service, Performance, Reliability™



*The industry's
most trusted supplier
of Specialty Films*

TECHNICAL DATA:

Vector's V2000

Ultra Metallics

A cast vinyl film series with excellent surface gloss, color depth and complete opacity. It provides dynamic graphic accents and can be used for RV and marine applications, automotive aftermarket graphics and striping, computerized signmaking, tradeshow exhibits and point-of-purchase displays.

Film Caliper	.003 inches	
Adhesive	Permanent Acrylic	
Release Liner	78# Kraft	
Printability	Printing not recommended	
Processability	Steel rule. Thermal and Rotary Die-cutting; Computerized Signmaking	
Outdoor Durability	5 years	
Dimensional Stability	.02 in. - 48hrs. at 150°F	
Temperature Ranges	Minimum application temperature is +40°F. Service temperature range is -50°F to +225°F.	
Adhesion	To stainless steel substrate - 20min. for 45 oz./in. 24hrs. for 64 oz./in.	
Storage Stability	2-year shelf life when stored at 73°F and 50% relative humidity.	
Elongation	80%	
Chemical Resistance	Anti-freeze (24hrs)	No Effect
	Detergent (24hrs)	No Effect
	Distilled Water (24hrs)	No Effect
	SAE 20 Motor Oil (24hrs)	No Effect
	Gasoline (1hr)	No Effect
	10% HCL (10min)	No Effect
	10% NH ₄ OH (10min)	No Effect
Standard Sizes	48"x50 yds. 48"x 250 yds. rolls	
Colors	Diamond, Topaz, Rose Quartz, Cinnabar, Amethyst, Beryl, Dark Amethyst, Azurite, Sapphire, Smoky Quartz, Light Onyx, Aventura, Cobalt Blue, Emerald Green, Fire Opal	



VECTOR[®]

925 Saw Mill River Rd., Yonkers, NY 10710

T: 914-963-8500 or 800-345-6027 • F: 914-963-9125 or 888-590-9125

www.vectorgraphics.com • sales@vectorgraphics.com