

VECTOR[®]

Service, Performance, Reliability™



*The industry's
most trusted supplier
of Specialty Films*

TECHNICAL DATA:

Vector's VMPI2012

Flexible White Matte PVC (Removable Adhesive)

A 3.4mil premium white matte flexible calendared PVC film coated with 200-4982 removable acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format printing systems.

Applications	Temporary interior or exterior signage, decals, nameplates, die-cut letters and point of purchase displays
Face Material	3.4 mils
Adhesive	.8 to 1 mils
Liner	6.7 mils
Adhesion	To glass - 5 to 15 oz./in. To standard test panels - 5 to 15 oz./in. PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.
Outdoor Durability	Removable up to 1-year under normal conditions
Temperature Ranges	Minimum application temperature is +40°F. Service temperature range is -40°F to +180°F.
Storage Stability	6-month shelf life when stored at 70°F and 50% relative humidity.
Dimensional Stability	Good
Water Resistance	Good Test if immersed
Humidity Resistance	Good
Solvent Resistance	Good



VECTOR[®]

925 Saw Mill River Rd., Yonkers, NY 10710

T: 914-963-8500 or 800-345-6027 • F: 914-963-9125 or 888-590-9125

www.vectorgraphics.com • sales@vectorgraphics.com