

VECTOR[®]

Service, Performance, Reliability™



*The industry's
most trusted supplier
of Specialty Films*

TECHNICAL DATA:

Vector's VMPI3002

Flexible Gloss White PVC (Permanent Adhesive)

A 3mil premium white gloss flexible calendared PVC film coated with 200-4990 permanent acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format printing systems.

Applications Interior or exterior signage, decals, nameplates, die-cut letters and point of purchase displays

Face Material 3 mils

Adhesive .8 to 1 mils

Liner 6.7 mils

Adhesion To stainless steel - 48 oz./in.

PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.

Outdoor Durability 3 years

Temperature Ranges Minimum application temperature is +40°F. Service temperature range is -40°F to +180°F.

Storage Stability 6-month shelf life when stored at 70°F and 50% relative humidity.

Dimensional Stability Good

Water Resistance Good
Test if immersed

Humidity Resistance Good

Solvent Resistance Good



VECTOR[®]

925 Saw Mill River Rd., Yonkers, NY 10710

T: 914-963-8500 or 800-345-6027 • F: 914-963-9125 or 888-590-9125

www.vectorgraphics.com • sales@vectorgraphics.com