

VECTOR[®]

Service, Performance, Reliability™



*The industry's
most trusted supplier
of Specialty Films*

TECHNICAL DATA:

Vector's VMPI4002/4003

Screen Printable White and Black Window Film

A 3 mil flexible vinyl designed for applications on the outside of windows. White and black perforated film has opacity built-in. Available with permanent and temporary adhesives. Temporary adhesive provides a good yet removable bond to smooth surfaces. Micro-perforation at 50%-removed area in combination with the black vinyl layer allows for a see-through optically clear view from inside the window.

Thickness	3 mil
Typical Film Caliper	6 mil
Typical Paper Caliper	10pt
Color	White and Black
Top Coating	Coated for compatibility with UV and solvent screen printing inks
Adhesive	Removable and permanent adhesives available
White Paper Carrier	#34 Super smooth 10pt board
Vacuum Barrier	.05 mil laminate
UV Durability	3 to 5 years
Temperature Ranges	Minimum application temperature is 50°F to 105°F. Service temperature range is -20°F to +160°F.
Application Surface	Smooth Glass
Adhesion	Mild when put on. Good after 48hrs. Removable for 1 year.
Storage Stability	1-year shelf life when stored at 70°F and 50% relative humidity.
View Through/UV filter	Optically clear view/filters 68% of UV rays.



VECTOR[®]

925 Saw Mill River Rd., Yonkers, NY 10710

T: 914-963-8500 or 800-345-6027 • F: 914-963-9125 or 888-590-9125

www.vectorgraphics.com • sales@vectorgraphics.com