

VECTOR[®]

Service, Performance, Reliability™



*The industry's
most trusted supplier
of Specialty Films*

TECHNICAL DATA:

Vector's VOL 2000

Lustre Overlaminating Film

Lustre Overlaminating Film is a pressure sensitive 3-mil luster PVC film with the optically clear 200-4990 permanent acrylic adhesive on a smooth paper liner. This vinyl film offers protection from abrasion, moisture and other environmental exposures. It is laminated by the cold laminating process without the addition of heat.

Applications	Lustre overlaminating film is designed to protect digital image prints and screen printed images for exhibit and display graphics. Can be used in most instances where an overlay with a semi-gloss finish is required.
Thickness	Film 3.0 mils. Adhesive 0.8 to 1.0 mil. Liner 4.0 mils. (Thickness variance +/- 10%)
Dimensional Stability	Good.
Temperature Ranges	Minimum application temperature is +40°F. Service temperature range is -40°F to +180°F.
Adhesion	To stainless steel - 48 oz./in. PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.
Light Transmission	Approximately 87%
Gloss 60° Gardner	Initial 40-60
Storage Stability	1-year shelf life when stored at 70°F and 50% relative humidity.
Product Codes	VOL 2000



VECTOR[®]

925 Saw Mill River Rd., Yonkers, NY 10710

T: 914-963-8500 or 800-345-6027 • F: 914-963-9125 or 888-590-9125

www.vectorgraphics.com • sales@vectorgraphics.com