

# VECTOR<sup>®</sup>

Service, Performance, Reliability™



*The industry's  
most trusted supplier  
of Specialty Films*

## TECHNICAL DATA:

### Vector's VOL4400

#### Floor Overlamine

A 5 mil slip resistant clear vinyl overlaminating film. This product is designed for use as a protective overlamine where graphics may experience a high exposure to scuffing, such as floor graphics, mouse pads and point-of-purchase displays.

Face Material	5.0 vinyl
Color and Finish	Slip resistant clear
Adhesive	1.2 mil permanent acrylic
Release Liner	1.2 mil polyester
Outdoor Durability	Indoor use only
Temperature Ranges	Minimum application temperature is +50°F. Service temperature range is -40°F to +180°F.
Adhesion	To stainless steel substrate - 15min. for 104 oz./in. 24hrs. for 139 oz./in.
Storage Stability	2-year shelf life when stored at 73°F and 50% relative humidity.
Flammability	Self-Extinguishing
Chemical Resistance	Detergent (24hrs) No Effect Distilled Water (24hrs) No Effect Gasoline (1hr) No Effect 10% HCL (10min) NA 10% NH <sub>4</sub> OH (10min) No Effect



## VECTOR<sup>®</sup>

925 Saw Mill River Rd., Yonkers, NY 10710

T: 914-963-8500 or 800-345-6027 • F: 914-963-9125 or 888-590-9125

[www.vectorgraphics.com](http://www.vectorgraphics.com) • [sales@vectorgraphics.com](mailto:sales@vectorgraphics.com)