

# VECTOR<sup>®</sup>

Service, Performance, Reliability™



*The industry's  
most trusted supplier  
of Specialty Films*

## TECHNICAL DATA:

### Vector's VSMW

#### White Spray Mask

A 3.5mil light white flexible vinyl with a moderate-peel adhesive is ideal for paint masking applications where removal occurs while painted part is still hot.

Face Material	3.5 mils
Adhesive	Removable acrylic, #522
Color	White Matte
Liner	78# claycoated bleached kraft
Elongation	3-4%
Tear Resistance	50 grams
Adhesion	To stainless steel - 15 min - 32 oz./in. 24 hr - 20 oz./in

PSTC-1 with 24-hour dwell at 73°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.

Temperature Ranges Minimum application temperature is +50°F.  
Service temperature range is -40°F to +180°F.

Storage Stability 2-year shelf life when stored at 73°F and 50% relative humidity.

Chemical Resistance	Anti-freeze (24hrs)	No Effect
	Detergent (24hrs)	No Effect
	Distilled Water (24hrs)	No Effect
	SAE 20 Motor Oil (24hrs)	No Effect
	Gasoline (1hr)	No Effect
	10% HCL (10min)	No Effect
	10% NH <sub>4</sub> OH (10min)	No Effect



## VECTOR<sup>®</sup>

925 Saw Mill River Rd., Yonkers, NY 10710

T: 914-963-8500 or 800-345-6027 • F: 914-963-9125 or 888-590-9125

[www.vectorgraphics.com](http://www.vectorgraphics.com) • [sales@vectorgraphics.com](mailto:sales@vectorgraphics.com)